



(1) Publication number:

0 464 328 A3

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 91106080.4

(51) Int. Cl.5: **H04N** 5/60

② Date of filing: 17.04.91

(30) Priority: 30.06.90 KR 9869

43 Date of publication of application: 08.01.92 Bulletin 92/02

Designated Contracting States:
 DK ES GB SE

Date of deferred publication of the search report:
 01.04.92 Bulletin 92/14

7) Applicant: SAMSUNG ELECTRONICS CO. LTD. 416 Maetan-Dong, Kwonsun-ku Suwon, Kyunggi-do(KR)

Inventor: Na, II-gu 3-406, Miryung, Apt., 416, Pisan-dong Anyang-city, Kyunggi-do(KR) Inventor: Lee, Wu-nyeon 422-204, Jugong Apt., Maetan-dong, Kwonsun-ku Suwon, Kyunggi-do(KR)


Representative: Wilhelm & Dauster Patentanwälte European Patent Attorneys Hospitalstrasse 8 W-7000 Stuttgart 1(DE)

- Multivoice broadcast search method and apparatus in NiCAM broadcasting receiver.
- (57) Disclosed are a multivoice broadcast search method and apparatus thereof comprising a tuner and demodulator 10 for processing radio frequency signals received from an antenna ANT and outputting FM audio signal FMS and NICAM broadcasting signals, a NICAM decoder and D/A converter 12 for receiving the NICAM signals from the tuner and demodulator 10, decoding and D/A converting the NICAM signals, so as to output a PCM L-channel signal PL and a PCM R-channel signal PR, and simultaneously supplying broadcasting state recognition signals MC2 and CTL to a microcomputer 14, first to third switching means for selecting and outputting a predetermined signal among the FM audio signal FMS, the PCM L-channel signal PL and the PCM R-channel signal PR under the control of the microcomputer 14, thereby the user can be informed what languages in the present multivoice broadcast are broadcast.

The multivoice broadcast search method comprises the steps of checking if the present received broadcast is a multivoice broadcast or not, storing logic values of the present broadcasting state, searching each of language broadcasts of the multivoice broadcast by setting the control signals to

predetermined values, holding them for a predetermined time and outputting each of the language broadcasts sequentially for a predetermined time, and returning to the stored original broadcasting state so as to output it.

FIG. 1



EUROPEAN SEARCH REPORT

Application Number

EP 91 10 6080

gory		th indication, where appropriate, want passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
A	ELEKTRONIK vol. 39, no. 6 pages 50 - 56; T. HILPERT MULTISTANDARD-AUDIO- * page 51, left column, line	ET AL.: 'DIGITALER CHIPSATZ'		H 04 N 5/60
Α	EP-A-0 239 760 (GRUNDIG) * abstract * * * page 6, line 26 - page 7, line 6 * *		1,4	
A	DE-A-3 843 451 (ROBER * column 1, line 60 - column line 56 * * -		1,4 ne 10 -	
,				
				TECHNICAL FIELDS SEARCHED (Int. CI.5)
			:	H 04 N
	·			
:				
	,			
	The present search report has	been drawn un for all claime		
	Place of search	Date of completion of	eparch	Examiner
	The Hague	06 February 9		SCHINNERL A.
Y: A:	CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same catagory A: technological background O: non-written disclosure		E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding	